


+ For swivel models add "S", for rigid model add "R" to end of base caster number.

Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
-------------------------	----------------------	---	-------------------------	----------------------	-------------------	---------------------

**Soft Rubber (01 Roller Bearing)**

	RR	4	2	220	5 5/8	1 11/16	6	16RR04201
		5	2	325	6 1/2	1 5/8	6 1/2	16RR05201
		6	2	350	7 1/4	1 3/4	6 3/4	16RR06201

**Monoprene Semi-Pneumatic (27 Radial Ball Bearing)**


	SZ	6	2	250	7 1/4	1 3/4	5 1/2	16SZ06227
		8	2	280	9 1/2	1 3/4	6 1/2	16SZ08227

For grey tread specify "SV" wheel code (example 16SV05228).


**Pneumatic (27 Radial Ball Bearing)**

	SF	8	2	210	9 1/2	1 3/4	6 1/2	16SF08227
---	----	---	---	-----	-------	-------	-------	-----------

**Eagle Polyurethane on Polypropylene (01 Roller Bearing)**


	EG	4	2	600	5 5/8	1 11/16	5 3/4	16EG04201
		5	2	900	6 1/2	1 5/8	5 1/2	16EG05201
		6	2	1100	7 1/4	1 3/4	8	16EG06201
		8	2	1200	9 1/2	1 3/4	10 1/4	16EG08201

**X-tra Soft (Flat Tread) (01 Roller Bearing)\***

	XS	4	2	350	5 5/8	1 11/16	5 1/4	16XS04201
		5	2	375	6 1/2	1 5/8	5 1/2	16XS05201
		6	2	600	7 1/4	1 3/4	6	16XS06201
		8	2	675	9 1/2	1 3/4	6 1/2	16XS08201


Prevenz™ antimicrobial models available (Add PREV).  
\*Precision Ball (28) and Delrin (51) Bearings available.  
Change "01" to other bearing code. Precision Ball example: 16XS04228. Delrin example: 16XS04251.

**X-tra Soft (Round Tread) (01 Roller Bearing)\***

	XR	6	2	450	7 1/4	1 3/4	5 1/2	16XR06201
		8	2	600	9 1/2	1 3/4	6 1/2	16XR08201

Prevenz™ antimicrobial models available (Add PREV).  
\*Precision Ball (28) and Delrin (51) Bearings available.  
Change "01" to other bearing code. Precision Ball example: 16XR04228. Delrin example: 16XR04251.


**Polypropylene (01 Roller Bearing)\***

	PB	4	1 1/2	400	5 5/8	1 11/16	4 1/2	16PB04101
		4	2	450	5 5/8	1 11/16	4 1/2	16PB04201
		5	1 1/2	450	6 1/2	1 5/8	5	16PB05101
		5	2	550	6 1/2	1 5/8	5	16PB05201
		6	1 1/2	550	7 1/4	1 3/4	5 3/4	16PB06101
		6	2	750	7 1/4	1 3/4	6	16PB06201


8 2 850 9 1/2 1 3/4 5 1/2 16PB08201

\*Delrin (51) Bearings or plain bore (41) models available.  
Change "01" to other bearing code. Delrin example: 16PB04251.

**White Polypropylene (41 Plain Bore)**

	PW	4	2	450	5 5/8	1 11/16	4 1/2	16PW04241
		5	2	550	6 1/2	1 5/8	5	16PW05241
		6	2	650	7 1/4	1 3/4	6	16PW06241


**High Temp Polypropylene (41 Plain Bore)**

	RW	4	2	500	5 5/8	1 11/16	5	16RW04241
		5	2	650	6 1/2	1 5/8	5 1/2	16RW05241
		6	2	700	7 1/4	1 3/4	6	16RW06241
		8	2	900	9 1/2	1 3/4	6 1/2	16RW08241

+ For swivel models add "S", for rigid model add "R" to end of base caster number.


Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Based on manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Approx. Wt. (Lbs)	Base Caster Number+
-------------------------	----------------------	---	-------------------------	----------------------	-------------------	---------------------

**Polyurethane on Aluminum (01 Roller Bearing)**

	PD	4	1 1/2	600	5 5/8	1 11/16	4 1/2	16PD04101
		4	2	700	5 5/8	1 11/16	5	16PD04201
		5	1 1/2	720	6 1/2	1 5/8	5	16PD05101
		5	2	1050	6 1/2	1 5/8	5 1/4	16PD05201
		6	2	1230	7 1/4	1 3/4	5 3/4	16PD06201


8 2 1250 9 1/2 1 3/4 7 16PD08201

**Polyurethane on Aluminum Round Tread (28 Precision Ball Bearing)**

	AX	4	2	700	5 5/8	1 11/16	5 1/2	16AX04228
		5	2	1000	6 1/2	1 5/8	6	16AX05228
		6	2	1250	7 1/4	1 3/4	7	16AX06228
		8	2	1250	9 1/2	1 3/4	9	16AX08228


85 Shore A

**Polyurethane on Aluminum Round Tread (28 Precision Ball Bearing)**

	PM	5	2	1000	6 1/2	1 5/8	6	16PM05228
		6	2	1250	7 1/4	1 3/4	7	16PM06228
		8	2	1250	9 1/2	1 3/4	9	16PM08228


95 Shore A

**Polyurethane on Aluminum Round Tread (28 Precision Ball Bearing)**

	PM 80A	5	2	1000	6 1/2	1 5/8	6	16PM0522880A
		6	2	1250	7 1/4	1 3/4	7	16PM0622880A
		8	2	1250	9 1/2	1 3/4	9	16PM0822880A


80 Shore A To Specify Rigid or Swivel, insert "R" or "S" before "80A".  
Example: 16PY08228R80A.

**Polyurethane on Cast Iron (01 Roller Bearing)**

	PY	3 1/4	1 5/8	420	4 1/4	1 3/4	4 1/4	16PY03101
		4	2	750	5 5/8	1 11/16	7	16PY04201
		5	2	1050	6 1/2	1 5/8	8	16PY05201
		6	2	1200	7 1/4	1 3/4	9 3/4	16PY06201
		8	2	1250	9 1/2	1 3/4	10	16PY08201


Made in the USA 80A Durometer available, add "80A" to end of caster number.  
80A capacity reduced by approximately 20%.  
Swivel example: 16PY06201S80A.

**Polyurethane on Polypropylene (01 Roller Bearing)**

	XA	4	2	600	5 5/8	1 11/16	4 1/4	16XA04201
		5	2	750	6 1/2	1 5/8	4 3/4	16XA05201
		6	2	900	7 1/4	1 3/4	5 1/2	16XA06201
		8	2	1000	9 1/2	1 3/4	7 1/2	16XA08201


Prevenz™ antimicrobial models available.  
Add PREV to end of caster number.

**V-Grooved Solid Polyurethane (02 Drawn Cup Roller Bearing)\***

	XV	4	2	300	5 5/8	1 11/16	4 1/2	16XV04202
		5	2	300	6 1/2	1 5/8	5	16XV05202
		6	2	300	7 1/4	1 3/4	5 1/4	16XV06202
		8	2	300	9 1/2	1 3/4	5 3/4	16XV08202

Made in the USA \*Delrin (52) Bearings models available.  
Change "02" to other bearing code. Example: 16XV04252.

**X-Treme™ Solid Polyurethane (01 Roller Bearing)\***

	XI	4	2	1000	5 5/8	1 11/16	5	16XI04201
		5	2	1000	6 1/2	1 5/8	5 1/2	16XI05201
		6	2	1000	7 1/4	1 3/4	6 1/4	16XI06201
		8	2	1000	9 1/2	1 3/4	8	16XI08201

Made in the USA \*Drawn Cup Roller (02), Bronze (22), Pedestal Precision (28), and Delrin (51) bearings available. Change "01" to other bearing code. Pedestal Precision example: 16XI04229.

Continue on next page >>