

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

| | | | | | | |
|-------------------------|----------------------|---|-------------------------|----------------------|-------------------|---------------------|
| | | | | | | |
| Wheel Diameter (Inches) | Tread Width (Inches) | Capacity (Lbs) (Based on manual operation) | Overall Height (Inches) | Swivel Lead (Inches) | Approx. Wt. (Lbs) | Base Caster Number+ |

| X-treme Plus Solid Polyurethane (28 Precision Ball Bearing) | | | | | | | |
|---|----|---|------|--------------------------------|---|----|-----------|
| XP | 8 | 3 | 2000 | 11 | 3 | 45 | 92XP08528 |
| | 10 | 3 | 2500 | 12 ⁷ / ₈ | 3 | 48 | 92XP10528 |



| Polyurethane on Cast Iron (09 Tapered Roller Bearing)* | | | | | | | |
|--|----|---|------|--------------------------------|-------------------------------|--------------------------------|-----------|
| PI | 8 | 3 | 2500 | 11 | 2 ¹ / ₂ | 43 ³ / ₄ | 92PI08509 |
| | 10 | 3 | 3000 | 12 ⁷ / ₈ | 2 ¹ / ₂ | 49 ¹ / ₂ | 92PI10509 |
| | 12 | 3 | 3500 | 14 ⁷ / ₈ | 2 ¹ / ₂ | 60 ¹ / ₂ | 92PI12509 |



*Roller (01) bearings available. Change "01" to other bearing code. Example: 92PI06501.

| Phenolic (01 Roller Bearing) | | | | | | | |
|------------------------------|----|---------------------------------|------|--------------------------------|-------------------------------|--------------------------------|-----------|
| TM | 8 | 3 | 2500 | 11 | 3 | 43 ¹ / ₄ | 92TM08501 |
| | 10 | 3 | 2900 | 12 ⁷ / ₈ | 3 | 46 ¹ / ₄ | 92TM10501 |
| | 12 | 3 | 3500 | 14 ⁷ / ₈ | 3 ¹ / ₂ | 49 ³ / ₄ | 92TM12501 |
| | 12 | 3 ¹ / ₂ * | 4000 | 14 ⁷ / ₈ | 3 ¹ / ₂ | 62 | 92TM12601 |



*3-1/2" and 4" tread width model has solid axle, all others hollow axle.

| Trionix™ High Impact Polymer (28 Precision Ball Bearing) | | | | | | | |
|--|----|---|------|--------------------------------|---|--------------------------------|-----------|
| NX | 8 | 3 | 4800 | 11 | 3 | 43 ¹ / ₄ | 92NX08528 |
| | 10 | 3 | 4800 | 12 ⁷ / ₈ | 3 | 46 | 92NX10528 |



| Cast Iron (01 Roller Bearing)* | | | | | | | |
|--------------------------------|----|----------------------------------|------|--------------------------------|-------------------------------|--------------------------------|-----------|
| CA | 8 | 3 | 2800 | 11 | 3 | 48 ¹ / ₄ | 92CA08501 |
| | 10 | 3 | 2800 | 12 ⁷ / ₈ | 3 | 53 ¹ / ₄ | 92CA10501 |
| | 12 | 3 | 2800 | 14 ⁷ / ₈ | 3 ¹ / ₂ | 59 | 92CA12501 |
| | 12 | 3 ¹ / ₂ ** | 4000 | 14 ⁷ / ₈ | 3 ¹ / ₂ | 74 | 92CA12601 |



*Tapered Roller (09) bearings available. Change "01" to other bearing code. Example: 92CA08509.

**3-1/2" and 4" tread width model has solid axle, all others hollow axle.

+ For swivel models add "S", for rigid model add "R" to end of base caster number.

| | | | | | | |
|-------------------------|----------------------|---|-------------------------|----------------------|-------------------|---------------------|
| | | | | | | |
| Wheel Diameter (Inches) | Tread Width (Inches) | Capacity (Lbs) (Based on manual operation) | Overall Height (Inches) | Swivel Lead (Inches) | Approx. Wt. (Lbs) | Base Caster Number+ |

| Drop Forged Steel (01 Roller Bearing)* | | | | | | | |
|--|----|---|------|--------------------------------|---|--------------------------------|-----------|
| FS | 8 | 3 | 4000 | 11 | 3 | 54 ³ / ₄ | 92FS08501 |
| | 10 | 3 | 4800 | 12 ⁷ / ₈ | 3 | 64 ¹ / ₄ | 92FS10501 |



* (09) Tapered Roller Bearings available. Change "01" to other bearing code. Example: 92FS08509.

| V-grooved Cast Iron (01 Roller Bearing) | | | | | | | |
|---|----|---|------|--------------------------------|---|----|-----------|
| VG | 8 | 3 | 2500 | 11 | 3 | 53 | 92VG08501 |
| | 10 | 3 | 3000 | 12 ⁷ / ₈ | 3 | 64 | 92VG10501 |



| Ductile Iron Crowned Tread (01 Roller Bearing)* | | | | | | | |
|---|----|---|------|--------------------------------|---|----|-----------|
| FR | 8 | 3 | 3500 | 11 | 3 | 49 | 92FR08501 |
| | 10 | 3 | 3500 | 12 ⁷ / ₈ | 3 | 55 | 92FR10501 |



*Tapered Roller (09) bearing available. Change "01" to other bearing code. Example: 92FR08509.

| Ductile Iron Flat Tread (01 Roller Bearing)* | | | | | | | |
|--|----|---|------|--------------------------------|---|----|-----------|
| FM | 8 | 3 | 3500 | 11 | 3 | 49 | 92FM08501 |
| | 10 | 3 | 3500 | 12 ⁷ / ₈ | 3 | 55 | 92FM10501 |



*Tapered Roller (09) bearing available. Change "01" to other bearing code. Example: 92FM08509.

| Ductile Iron V-Groove Tread (01 Roller Bearing)* | | | | | | | |
|--|----|---|------|--------------------------------|---|----|-----------|
| VM | 8 | 3 | 3500 | 11 | 3 | 49 | 92VM08501 |
| | 10 | 3 | 3500 | 12 ⁷ / ₈ | 3 | 55 | 92VM10501 |



*Tapered Roller (09) bearing available. Change "01" to other bearing code. Example: 92VM08509.

CUSTOM FABRICATION

This is not a one-size-fits-all business. In fact, many of our orders require custom fabrication.

If you can't find the right caster for your special application, put the Albion engineering team to work. We will create the perfect solution for your moving problem.



See pages 16-17