

115 Kingpinless Dual Wheel Casters

CAPACITY TO 2000




The 115 Series is a dual wheel version of our popular 110 Contender Kingpinless Series, with the addition of a third full leg for even greater durability. This remarkably durable dual wheel series provides easy turning and a sturdy footprint you can rely on.


TYPICAL APPLICATIONS

- Dollies
- Dough troughs
- Platform trucks
- Tow line
- Utility carts
- Tooling fixtures
- Scrap metal carriers

MOUNTING OPTIONS Standard Plate



SWIVEL CROSS SECTION



Drive lasting results with

CG-MAX EFFICIENCY WHEEL™



WHEEL SELECTION



CG-MAX
Orange or Maroon Maximum Efficiency Wheels



PM
Polyurethane Round Tread on Aluminum Core (Green)



PD
Polyurethane on Aluminum Core



PF
Polyurethane on Heavy Duty Cast Iron Core



NX
Trionix™ High Impact Polymer



TM
Phenolic



FEATURES

- **Dual Wheel:** 115 series is similar to 110 Series Contender, but adds a wheel and a fork leg for extra strength
- **3 Year warranty**
- **Top Plate:** 5/16" AISI 1045 steel welded and heat treated for longer life
- **Yoke Base:** Notched AISI 1045 steel with extra leg for greater durability.
- **Swivel Section:** One row of 3/8" ball bearings mounted in a **heat treated** precision machined raceway. Zerk in swivel section
- **Axle:** 1/2" diameter hollow axle with zerk fitting on roller and tapered bearing models (Solid axle on precision ball models)
- **Finish:** Zinc plating
- Alternate or custom caster configurations available

BEARING OPTIONS



RIG OPTIONS

- **Optional swivel leads** of 2-1/4" for 8" casters. To order, add **X** to end of model number. Consult factory for specification support, as load capacities may reduce based on application or equipment design.



PLB Integrated Brake specify (6" & 8" diameter models only) **PLB**

Poly Cam Integrated Brake specify **P**



Add **TO** to end of Caster Number to specify integrated toe guard. Standard model toe guards are 1/2" from floor

SWIVEL LOCKS



Hand Operated Swivel Lock specify **L**

Base Swivel Caster Number In Chart For rigid models change "S" to "R" at end of base caster number.

115 Kingpinless Dual Wheel						Base Swivel Caster Number Precision Ball (28)	Base Swivel Caster Number Pedestal Precision Ball (29)
Wheel Diameter (Inches)	Tread Width (Inches)	Capacity (Lbs) (Rolls for manual operation)	Overall Height (Inches)	Swivel Lead (Inches)	Wheel Type		
4	2	1600	5 3/4	1.188	CG-MAX Polyurethane (Orange)	115AN04228S	
4	2	1600	5 3/4	1.188	CG-MAX Polyurethane (Maroon)	115AX04228S	
4	2	1600	5 3/4	1.188	Phenolic		115TM04229S
4	2	1400	5 3/4	1.188	Polyurethane on Aluminum		115PD04229S
4	2	2000	5 3/4	1.188	Trionix™ High Impact Polymer	115NX04228S	
5	2	2000	6 3/4	1.5	CG-MAX Polyurethane (Orange)	115AN05228S	
5	2	2000	6 3/4	1.5	CG-MAX Polyurethane (Maroon)	115AX05228S	
5	2	2000	6 3/4	1.5	Round Polyurethane on Alum. (Green)	115PM05228S	
5	2	2000	6 3/4	1.5	Polyurethane on Aluminum		115PD05229S
5	2	2000	6 3/4	1.5	Phenolic		115TM05229S
5	2	2000	6 3/4	1.5	Trionix™ High Impact Polymer	115NX05228S	
6	2	2000	7 3/4	1.563	CG-MAX Polyurethane (Orange)	115AN06228S	
6	2	2000	7 3/4	1.563	CG-MAX Polyurethane (Maroon)	115AX06228S	
6	2	2000	7 3/4	1.563	Round Polyurethane on Alum. (Green)	115PM06228S	
6	2	2000	7 3/4	1.563	Polyurethane on Aluminum		115PD06229S
6	2	2000	7 3/4	1.563	Polyurethane on Heavy Duty Cast Iron	115PF06228S	
6	2	2000	7 3/4	1.563	Phenolic		115TM06229S
6	2	2000	7 3/4	1.563	Trionix™ High Impact Polymer	115NX06228S	
8	2	2000	10 1/8	2.250	CG-MAX Polyurethane (Orange)	115AN08228S	
8	2	2000	10 1/8	2.250	CG-MAX Polyurethane (Maroon)	115AX08228S	
8	2	2000	10 1/8	2.250	Round Polyurethane on Alum. (Green)	115PM08228S	
8	2	2000	10 1/8	2.250	Polyurethane on Aluminum		115PD08229S
8	2	2000	10 1/8	2.250	Polyurethane on Heavy Duty Cast Iron	115PF08228S	
8	2	2000	10 1/8	2.250	Phenolic		115TM08229S
8	2	2000	10 1/8	2.250	Trionix™ High Impact Polymer	115NX08228S	

See 110 Series section for wheel appearance and descriptions.