Trans-forma® LT Wheels

Flat or Round Black Tread

Capacity up to 500 lbs each

Wheel Options

 Pedestal Precision Ball Bearing (PPBB) also available in stainless steel (consult factory).



Made with Grade 5 recyclable material to help protect our environment, this is the perfect lower cost replacement for moldon rubber or TPR wheels. The LT wheel is manufactured using co-injection molding on our state of the art equipment that chemically bonds the TPE material to a sturdy polyolefin core. The multi-purpose design is well suited for a variety of applications including (but not limited to): dumpster/trash bins, lumber carts and flower carts.

Temperature range: -45°F to +180°F. **Hardness:** 80(±5) Durometer Shore A scale.

Colson Trans-forma LT Wheels • Capacity up to 500 lbs each

Flat Tread Models				Wheel			Spanner Bushing				
Wheel Dia.	Tread Width	Capacity Each (Pounds)	Bearing	Wheel Model Number	Bearing Bore	Bore Less Bearing	Hub Length	Bore	Length	Thread Guard TG1: Metal	Weight (Pounds)
4"	2"	400	Delrin	5.00004.4B1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.12	1
			PPBB	5.00004.4B5	1/2"	1 ³ /16"	2 ⁷ /16"	_	_	TG1: 57852.12	11
			Roller	5.00004.4B9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.12	1
			Less Bearing	5.00004.4B6	-	1 ³ /16"	2 ³ /16"	-	-	TG1: 57852.12	1
5"	2"	450	Delrin	5.00005.4B1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 52007.94	1 ¹ /4"
			PPBB	5.00005.4B5	1/2"	1 ³ /16"	2 ⁷ /16"	_	_	TG1: 52007.94	1 ¹ /4"
			Roller	5.00005.4B9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 52007.94	1 ¹ /4"
			Less Bearing	5.00005.4B6	-	1 ³ /16"	2 ³ /16"	-	-	TG1: 52007.94	1 ¹ /4"
6"	2"	500	Delrin	5.00006.4B1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			PPBB	5.00006.4B5	1/2"	1 ³ /16"	2 ⁷ /16"	_	_	TG1: 57852.45	1 ³ /8"
			Roller	5.00006.4B9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			Less Bearing	5.00006.4B6	_	1 ³ /16"	2 ³ /16"	_	_	TG1: 57852.45	1 ³ /8"
Round Tread Models											
6"	2"	400	Delrin	5.00006.5B1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			PPBB	5.00006.5B5	1/2"	1 ³ /16"	2 ⁷ /16"	_	_	TG1: 57852.45	1 ³ /8"
			Roller	5.00006.5B9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			Less Bearing	5.00006.5B6	-	1 ³ /16"	2 ³ /16"	-	_	TG1: 57852.45	1 ³ /8"

Trans-forma® Wheels

Flat or Round Grey Tread

Capacity up to 600 lbs each

Wheel Options

 Pedestal Precision Ball Bearing (PPBB) also available in stainless steel (consult factory).



This quiet rolling, non-marking marvel rejects floor debris while providing a shock absorbing, cushioned ride that helps protect your valuable cargo. It's the perfect lower cost replacement for more expensive TPE and TPR wheels. The Trans-forma wheel is manufactured using co-injection molding on our state of the art equipment that chemically bonds the TPE material to a sturdy polyolefin core. The multi-purpose design is well suited for a variety of applications including (but not limited to): laundry carts, medical equipment, electronic equipment, material handling carts and nursery carts.

Temperature range: -45°F to +180°F. **Hardness:** 65(±5) Durometer Shore A scale.

Colson Trans-forma • Capacity up to 600 lbs each

			,								
Flat Tread Models					Wheel			Spanner Bushing			
Wheel Dia.	Tread Width	Capacity Each (Pounds)	Bearing	Wheel Model Number	Bearing Bore	Bore Less Bearing	Hub Length	Bore	Length	Thread Guard TG1: Metal	Weight (Pounds)
4"	2"	400	Delrin	5.00004.4E1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.12	1
			PPBB	5.00004.4E5	1/2"	1 ³ /16"	2 ⁷ /16"	_	_	TG1: 57852.12	1
			Roller	5.00004.4E9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.12	1
			Less Bearing	5.00004.4E6	-	1 ³ /16"	2 ³ /16"	-	_	TG1: 57852.12	1
5"	2"	500	Delrin	5.00005.4E1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 52007.94	1 ¹ /4"
			PPBB	5.00005.4E5	1/2"	1 ³ /16"	2 ⁷ /16"	_	_	TG1: 52007.94	1 ¹ /4"
			Roller	5.00005.4E9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 52007.94	1 ¹ /4"
			Less Bearing	5.00005.4E6	-	1 ³ /16"	2 ³ /16"	_	_	TG1: 52007.94	1 ¹ /4"
6"	2"	600	Delrin	5.00006.4E1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			PPBB	5.00006.4E5	1/2"	1 ³ /16"	2 ⁷ /16"	-	-	TG1: 57852.45	1 ³ /8"
			Roller	5.00006.4E9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			Less Bearing	5.00006.4E6	-	1 ³ /16"	2 ³ /16"	-	-	TG1: 57852.45	1 ³ /8"
Round Tread Models											
6"	2"	450	Delrin	5.00006.5E1	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			PPBB	5.00006.5E5	1/2"	1 ³ /16"	2 ⁷ /16"	_	_	TG1: 57852.45	1 ³ /8"
			Roller	5.00006.5E9	3/4"	1 ³ /16"	2 ³ /16"	1/2"	2 ⁷ /16"	TG1: 57852.45	1 ³ /8"
			Less Bearing	5.00006.5E6	-	1 ³ /16"	2 ³ /16"	-	_	TG1: 57852.45	1 ³ /8"