Crown and Round Tread

Capacity up to 1200 lbs each

Triumph wheels are a new generation of ergonomically friendly wheels available only from Colson. The wheels include precision ball bearings for maximum rolling ease. Triumph's polyurethane tread is chemically and mechanically bonded to an aluminum core. Wheels come in various colors and durometers. You can choose crown or round tread designs. These wheels are specially designed for tow-line application. Wheels do not skid or mark floors.

Crown Tread

Temperature Range: -40°F to +180°F.



\\(\frac{1}{2} = 2 \cdot \)	Tread Width	Capacity Each (Pounds)	Bearing	Wheel Model Number		Hat Bushing		
Wheel Dia.					Bore	Length	Weight (Pounds)	
Red Polyurethane • Durometer 75 Shore A								
8"	2"	1200	Prec. Ball	5.00008.93TS	1/2"	2 ⁷ /16"	43/8	
Brown Polyurethane ● Durometer 90 Shore A 8" 2" 1200 Prec. Ball 5.00008.93TF 1/2" 2 ⁷ /16" 4 ³ /8								
8"	2"	1200	Prec. Ball	5.00008.93TF	1/2"	2 ⁷ /16"	4 ³ / ₈	

Round Tread



	Tread Width	Capacity Each (Pounds)	Bearing	Wheel Model Number	Top Hat Spanner Bushing			
Wheel Dia.					Bore	Length	Weight (Pounds)	
Red Polyurethane • Durometer 80 Shore A								
6"	2"	900	Prec. Ball	5.00006.96TS	1/2"	2 ⁷ /16"	3	
8"	2"	1200	Prec. Ball	5.00008.96TS	1/2"	27/16"	43/8	
Blue Polyurethane • Durometer 95 Shore A								
6"	2"	900	Prec. Ball	5.00006.96TF	1/2"	27/16"	3	
8"	2"	1200	Prec. Ball	5.00008.96TF	1/2"	27/16"	43/8	

Conquest™ Wheels

Ergomonic Towable

Capacity up to 1500 lbs. each





Colson's new Conquest wheel is the ultimate in ergonomic performance. Independent testing proves the Conquest wheel requires 20% LESS force to move than comparative wheels. This reactive polyurethane wheel tread is chemically and mechanically molded onto a lightweight aluminum wheel core. Count on this wheel to glide quietly across even debris covered floors, while maintaining the durability to carry heavy loads (up to 1500 lbs. each).

Ton Hat

Temperature range: -45°F to +180°F. **Hardness:** 85(±5) Durometer Shore A scale.

Massal	1	Capacity	l I	l	Spanner Bushing		
Wheel Dia.	Tread Width	Each (Pounds)	Bearing	Wheel Model Number	Bore	Length	Weight (Pounds)
4"	2"	800	Prec. Ball	5.00004.9PC	1/2"	2 ⁷ /16"	3 ¹ /4
5"	2"	1000	Prec. Ball	5.00005.9PC	1/2"	27/16"	33/8
6"	2"	1250	Prec. Ball	5.00006.9PC	1/2"	27/16"	31/2
8"	2"	1500	Prec. Ball	5.00008.9PC	1/2"	2 ⁷ /16"	33/4