
Floor Lock Brakes







Floor Lock Brake Installation



Recommended Floor Lock mounting position using four swivel casters.



Recommended Floor Lock mounting position using two swivel and two rigid casters.

Colson Floor Lock Brakes are designed for use on level surfaces and are not recommended for use on inclined surfaces. It is important to select a floor lock model that clears the floor when retracted. To adapt a floor lock brake to your present equipment, select a model with an extended height 1/16" to 1/4" greater than the overall height of the caster.

Features

- Heavy duty industrial strength construction
- Foot pedal easily activates lock with foot pressure
- Non-slip, non-skid rubber brake pad holds securely on smooth or irregular floor. Designed for use on level surfaces.
- Durable, high-compression spring for heavy loads
- Conveniently located release bar retracts brake instantly with slight toe pressure to either side of the bar
- Attractive zinc plated finish

Floor Lock Specifications

21/2" x 35/8" TOP PLATE MODELS (2 & 3 Series Casters)

| MODEL NO. | 9.06002.03 | 9.06253.04 | 9.06002.05 |
|-----------------------|---|--|------------|
| Extended Height A | 4 ¹⁵ / ₁₆ " | 5 ¹⁷ / ₃₂ " | 67/32" |
| Retracted Height B | 37/8" | 4 ¹ / ₂ " | 511/64" |
| Top Plate Size | 2¹/₂" x 3⁵/₅" | | |
| Bolt Hole Spacing | 1 ³ / ₄ " x 2 ⁷ / ₈ " to 3" | | |
| Bolt Hole Size | 5/ ₁₆ " Slotted | | |
| Weight | 23/4 lbs. | 23/4 lbs. | 23/4 lbs. |
| Used with Caster Fork | 2.03208 | 2.04208 | 2.05008 |
| Model Numbers | 2.03256 | 2.04256 | 2.05256 |
| | 3.00308 | 3.00408 | |
| | 3.00317 | 3.00417 | |



Easy to engage.



Easy to disengage.

4" x 41/2" TOP PLATE MODELS (3, 4 & 6 Series Casters)

| 9.06045.04 | 9.06253.05 | 9.06045.06 | 9.06025.08 | | |
|--------------------------------------|------------|-----------------------------------|-----------------------------------|--|--|
| 57/8" | 643/64" | 73/4" | 9 ²³ / ₃₂ " | | |
| 415/16" | 535/64" | 6 ²¹ / ₃₂ " | 85/8" | | |
| 4" x 4 ¹ / ₂ " | | | | | |
| 3" x 3" to 25/8" x 35/8" | | | | | |
| 3/8" Slotted | | | | | |
| $3^{1}/_{2}$ lbs. | 41/2 lbs. | 41/2 lbs. | 43/4 lbs. | | |
| 4.04108 | 3.00508 | 3.00608 | 4.08198 | | |
| 4.04109 | 3.00517 | 3.00617 | 4.08199 | | |
| 4.04408 | 4.05108 | 4.06108 | 4.08499 | | |
| 4.04409 | 4.05109 | 4.06109 | 4.08299 | | |
| 4.04189 | 4.05408 | 4.06408 | 4.08189 | | |
| 6.04208 | 4.05409 | 4.06409 | 6.08258 | | |
| 6.04209 | 4.05189 | 4.06189 | 6.08259 | | |
| 6.04279 | 6.05208 | 6.06208 | 6.08298 | | |
| | 6.05209 | 6.06209 | 6.08299 | | |
| | 6.05279 | 6.06258 | | | |
| | | 6.06259 | | | |
| | | 6.06299 | | | |
| | | | | | |

Floor Lock Replacement Pad 34013.26