

Features


- Zinc plated finish is attractive and durable
- Full double ball hardened raceways for better performance and greater durability
- ⁵/₁₆" shouldered axle with ¹/₄" nut
- "Colson 45" multi-temp grease lubricates in extreme hot and cold temperatures

Standard Mounting

- For use on wood furniture that can accept a 3/8" diameter hole approximately 1 5/8" deep
- Stem Size: 5/16" diameter x 1 1/2" long grip neck
- Standard No. 20 pressed steel adapter (Part #50011) with toothed base is supplied







Colson 1 Series Casters • Wood Furniture Stem • Capacity to 75 lbs

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Stem Caster Models	Load Height	Swivel Radius	Weight (Pounds)
1 ⁵ /8"	7/8"	60	Performa Rubber	Delrin	1.01652.441	21/2"	1 ³ /4"	1/2
		75	Polyolefin	Delrin	1.01652.52	21/2"	13/4"	1/2
2"	7/8"	75	Performa Rubber	Delrin	1.02252.441	2 ¹¹ /16"	1 ¹⁵ /16"	1/2
			Polyolefin	Delrin	1.02252.52	211/16"	1 ¹⁵ /16"	1/2
			Cushion Rubber	Ball	1.02252.45	211/16"	1 ¹⁵ /16"	1/2
			Hard Rubber	Ball	1.02252.55	2 ¹¹ /16"	1 ¹⁵ /16"	1/2
3"	7/8"	75	Performa Rubber	Delrin	1.03052.441	313/16"	2 ⁹ /16"	3/4
			Polyurethane HI-TECH	Delrin	1.03052.91	3 ¹³ / ₁₆ "	2 9/16"	3/4
			Polyolefin	Delrin	1.03052.53	313/16"	2 ⁹ /16"	3/4

Caster Brake



Side Lock

(See page 96) Available on all 3" models. Field installable (Specify BRK3; Example: 1.03052.53 BRK3).

Fork Options

NSF Listed for Food Service Industry All models except thread guards.

Forks Only

To order caster forks only use 1st 6 digits of model numbers (Example: 1.01652).

Wheel Selection

Performa Flat Tread

Polyolefin

Polyurethane HI-TECH

Cushion Rubber Hard Rubber



See the Performa Advantage on Page 67.

Wheel Option

Thread Guards

(See page 108) Available on all 3" models. Brake & NSF options cannot be used with thread guards (Specify **TG1** for metal; Example: 1.01652.441 TG1).