











Features

- · Corrosion resistant zinc finish
- · Hardened double ball raceways
- Operating temperature rating -45°F to 180°F

Ultra-tough, thermoplastic wheel resists hard impacts and supports high dynamic load

Typical Applications

Vending machines, computer racks, server cabinets or anywhere overall load height is restricted


Performance Options

• Consult factory for rigid, brake and additional finish options




Business Machine Casters • 500 lb Top Plate

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Swivel Top Plate Caster Models	Load Height	Swivel Radius	Weight lbs
3"	1 ¹³ /16"	500	Glass Filled Nylon	Roller	S4.3305.351	41/8"	23/4"	2 ¹ / ₄



Business Machine Casters • 700 lb Top Plate

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Swivel Top Plate Caster Models	Load Height	Swivel Radius	Weight Ibs
3"	1 ¹³ /16"	700	Glass Filled Nylon	Roller	S4.3307.351	3 31/32"	2 3/4"	2 ¹ /2



Business Machine Casters • 1200 lb Top Plate

Wheel Dia.	Tread Width	Capacity Each (Pounds)	Wheel Descriptions	Wheel Bearing	Swivel Top Plate Caster Models	Load Height	Swivel Radius	Weight lbs
3"	1 ¹³ /16"	1200	Glass Filled Nylon	Roller	S4.3312.351	4 ¹ /8	2 1/2	3

