

Triumph® Wheels

Ergonomic
Towable

Round Tread

Capacity up to 1200 lbs each

Triumph wheels are a new generation of ergonomically friendly wheels available only from Colson. The wheels include precision ball bearings and round treads for maximum rolling ease. Triumph's polyurethane tread is chemically and mechanically bonded to an aluminum core. Wheels come in various colors and durometers. These wheels are specially designed for tow-line application. Wheels do not skid or mark floors.

Temperature Range: -40°F to +180°F.

Round Tread



Wheel Dia.	Tread Width	Capacity Each (Pounds)	Bearing	Wheel Model Number	Top Hat Spanner Bushing		Weight (Pounds)
					Bore	Length	
Red Polyurethane • Durometer 80 Shore A							
6"	2"	900	Prec. Ball	5.00006.96TS	1/2"	27/16"	3
8"	2"	1200	Prec. Ball	5.00008.96TS	1/2"	27/16"	4 ³ / ₈
Blue Polyurethane • Durometer 95 Shore A							
6"	2"	900	Prec. Ball	5.00006.96TF	1/2"	27/16"	3
8"	2"	1200	Prec. Ball	5.00008.96TF	1/2"	27/16"	4 ³ / ₈

CG-MAX Efficiency Wheels™

Capacity up to 1500 lbs. each



Maximum Efficiency Wheel

- Ergonomic to the MAX
- Wheel Longevity to the MAX
- Your Purchasing Power to the MAX
- Towable

The CG-MAX wheel was designed and formulated to outperform, outlast, and take customer efficiency to the MAX. With best-in-class ergonomics and durability, this versatile polyurethane on aluminum wheel will drive new value into your operations.

Temperature range: -45°F to +180°F.

Hardness: 85(±5) Durometer Shore A scale.

- Our most advanced polyurethane wheel
- ANSI:ICWM tested to outlast and outperform the competition
- Best-in-class ergonomics increase user safety and reduce fatigue
- Patent pending self-retaining top hats reduce environmental and assembly waste



Wheel Dia.	Tread Width	Capacity Each (Pounds)	Bearing	Wheel Model Number	Top Hat Spanner Bushing		Weight (Pounds)
					Bore	Length	
Orange Round Tread Polyurethane CG-MAX • Durometer 85 Shore A							
4"	2"	800	Prec. Ball	5.00004.9NC	1/2"	27/16"	1 ¹ / ₂
5"	2"	1000	Prec. Ball	5.00005.9NC	1/2"	27/16"	2
6"	2"	1250	Prec. Ball	5.00006.9NC	1/2"	27/16"	3
8"	2"	1500	Prec. Ball	5.00008.9NC	1/2"	27/16"	4
Maroon Round Tread Polyurethane CG-MAX • Durometer 85 Shore A							
4"	2"	800	Prec. Ball	5.00004.9PC	1/2"	27/16"	1 ¹ / ₂
5"	2"	1000	Prec. Ball	5.00005.9PC	1/2"	27/16"	2
6"	2"	1250	Prec. Ball	5.00006.9PC	1/2"	27/16"	3
8"	2"	1500	Prec. Ball	5.00008.9PC	1/2"	27/16"	4

Visit colsoncaster.com/CG-MAX for additional information and CAD models.