

# NEXT GENERATION NYLON ANTISTATIC (NA)

PLATE • HOLLOW RIVET • GRIP RING • THREADED  
FREE SWIVEL • TOTAL LOCK • DIRECTION LOCK



## APPLICATIONS

- Food Service
- Case Carts
- Utility Carts
- Hospital Equipment
- Institutional Equipment
- Store Fixtures
- Medical equipment

Precision sealed ball bearing raceway design for smooth, quiet maintenance free ride.

## FEATURES

- Maintenance free
- Sealed precision bearing raceway, smooth and quiet
- **Total Lock Brake** models lock both swivel and wheel
- Directional lock models lock swivel only (helps with steering)
- Wheels feature sealed precision ball bearings and full thread guards
- Resistance to most chemicals
- Zinc plated top plate
- Recessed axle with plastic cap covers

Antistatic models can help protect your equipment

## FREE SWIVEL MODELS

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm)* | Swivel Radius Inches (mm) | Wheel Bearing  | Model Number       |
|-------------------------|----------------------|-------------------|----------------|--------------------------|---------------------------|----------------|--------------------|
| 3                       | 1-1/4                | QuikStart TPR     | 180            | 4-1/4" (108)             | 2-13/16" (72)             | Precision Ball | NA-03QDP-125-SW-__ |
| 4                       | 1-1/4                | QuikStart TPR     | 220            | 5-3/4" (146)             | 3-7/16" (87)              | Precision Ball | NA-04QDP-125-SW-__ |
| 5                       | 1-1/4                | QuikStart TPR     | 240            | 6-7/8" (174)             | 4" (102)                  | Precision Ball | NA-05QDP-125-SW-__ |
| 6                       | 1-1/4                | QuikStart TPR     | 264            | 7-11/16" (195)           | 4-9/16" (116)             | Precision Ball | NA-06QDP-125-SW-__ |



Rigid models available. Change SW to RG.

## TOTAL LOCK MODELS

(LOCKS WHEEL AND SWIVEL)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm)* | Swivel Radius Inches (mm) | Wheel Bearing  | Model Number       |
|-------------------------|----------------------|-------------------|----------------|--------------------------|---------------------------|----------------|--------------------|
| 3                       | 1-1/4                | QuikStart TPR     | 180            | 4-1/4" (108)             | 3-3/4" (95)               | Precision Ball | NA-03QDP-125-TL-__ |
| 4                       | 1-1/4                | QuikStart TPR     | 220            | 5-3/4" (146)             | 4-7/16" (112)             | Precision Ball | NA-04QDP-125-TL-__ |
| 5                       | 1-1/4                | QuikStart TPR     | 240            | 6-7/8" (174)             | 4-7/16" (112)             | Precision Ball | NA-05QDP-125-TL-__ |
| 6                       | 1-1/4                | QuikStart TPR     | 264            | 7-11/16" (195)           | 4-9/16" (116)             | Precision Ball | NA-06QDP-125-TL-__ |



## DIRECTION LOCK MODELS

(LOCKS WHEEL AND SWIVEL)

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm)* | Swivel Radius Inches (mm) | Wheel Bearing  | Model Number       |
|-------------------------|----------------------|-------------------|----------------|--------------------------|---------------------------|----------------|--------------------|
| 3                       | 1-1/4                | QuikStart TPR     | 180            | 4-1/4" (108)             | 3-3/4" (95)               | Precision Ball | NA-03QDP-125-DL-__ |
| 4                       | 1-1/4                | QuikStart TPR     | 220            | 5-3/4" (146)             | 4-7/16" (112)             | Precision Ball | NA-04QDP-125-DL-__ |
| 5                       | 1-1/4                | QuikStart TPR     | 240            | 6-7/8" (174)             | 4-7/16" (112)             | Precision Ball | NA-05QDP-125-DL-__ |
| 6                       | 1-1/4                | QuikStart TPR     | 264            | 7-11/16" (195)           | 4-9/16" (116)             | Precision Ball | NA-06QDP-125-DL-__ |


New rigid brake models now available on 5" models. Change TL to RB

\*For non-plate models subtract approximately 1/8" from load height.

Specify Fitting code ↑

## FITTING OPTIONS

Swivel Top  
Plate Pattern



### Hollow Rivet


HKU1 unassembled  
HKO1 assembled  
1/2 I.D.

### Grip Ring Stem


GR01



GR02



GR09



### Threaded Stem

TS02



TS02



Other fittings available such as RS01, RS03, SQ01 and SQ03. See page 4-5 for more options.