

PRIMACY TWIN WHEEL (PT)

FREE SWIVEL • TOTAL LOCK •
TOTAL/DIRECTION LOCK COMBO

NEW



PT-05PYP-283-TL-CL02



PT-06PYP-283-TL-CL01

- APPLICATIONS**
- Hospital Beds
 - Stretchers
 - Mobile Ultrasound Equipment
 - OR Beds
 - Radiology Tables
 - Medical Chairs/Recliners
 - ICU Beds
 - Care Beds

- FEATURES**
- Smooth integrated central locking selection for free swivel, total lock, and directional (steer) lock.
 - Precision bearings in swivel section and sealed precision bearings in wheels.
 - Durable twin non-marking polyurethane wheel treads
 - High quality synthetic cover over die cast aluminum frame
 - Antistatic Option Available
 - Caster meets ISO Standard 22882: 2004 Caster & Wheels - Requirements for Casters for Hospital Beds.

CENTRAL LOCKING TOTAL LOCK MODELS

Wheel Diameter mm (in)	Tread Width mm (in)	Wheel Description*	Capacity (Lbs)	Load Height mm (in)	Swivel Radius mm (in)	Wheel Bearing	Model Number
100 (4)	64 (2-1/2)	Polyurethane Gray	275	129 (5-5/64)	81 (3-1/4)	Precision Ball	PT-04PYP-283-TL-CL__
123 (5)	64 (2-1/2)	Polyurethane Gray	286	150 (5-29/32)	92.5 (3-41/64)	Precision Ball	PT-05PYP-283-TL-CL__
150 (6)	64 (2-1/2)	Polyurethane Gray	330	175 (6-29/32)	115 (4-17/32)	Precision Ball	PT-06PYP-283-TL-CL__

CENTRAL LOCKING DIRECTIONAL AND TOTAL LOCK COMBO


100 (4)	64 (2-1/2)	Polyurethane Gray	275	129 (5-5/64)	81 (3-1/4)	Precision Ball	PT-04PYP-283-DT-CL__
123 (5)	64 (2-1/2)	Polyurethane Gray	286	150 (5-29/32)	92.5 (3-41/64)	Precision Ball	PT-05PYP-283-DT-CL__
150 (6)	64 (2-1/2)	Polyurethane Gray	330	175 (6-29/32)	115 (4-17/32)	Precision Ball	PT-06PYP-283-DT-CL__

CENTRAL LOCKING FREE SWIVEL MODELS


100 (4)	64 (2-1/2)	Polyurethane Gray	275	129 (5-5/64)	81 (3-1/4)	Precision Ball	PT-04PYP-283-SW-RS__
123 (5)	64 (2-1/2)	Polyurethane Gray	286	150 (5-29/32)	92.5 (3-41/64)	Precision Ball	PT-05PYP-283-SW-RS__
150 (6)	64 (2-1/2)	Polyurethane Gray	330	175 (6-29/32)	115 (4-17/32)	Precision Ball	PT-06PYP-283-SW-RS__

*For Antistatic caster models replace PYP in part number with APP.

Locking Models




- Stem diameter 27.8mm
- Two locking hole options
- Locking hole in line or across direction of travel
- Four fixing holes
- Snap-on adapter sleeves options for different tube dimensions
- Standard cam (41°/52°)



- Stem diameter 32mm
- Two locking hole options available
- Locking hole in line or across direction of travel
- Four fixing holes
- Standard cam 30°


Steering (locks swivel)



Free Swivel Models



27.8mm x 45mm for tubular frame with 28mm ID



32mm x 45mm For tubular frame with 32mm ID