

# MEDCASTER MODEL NUMBERING SYSTEM

Below example is a Nylon Light Grey (NG) caster that has a 5" diameter QuickStart wheel with a dark grey tread, thread guard and Precision Ball bearing. The tread width is 1-1/4" wide. The fork type is swivel. The fitting type is threaded stem (1/2"-13NC x 1-1/2").

**NG - 05 QDP - 125 - SW - TS03**

<b>AC</b> Autoclave	<b>OP</b> Optimus	<b>Wheel Type</b>	<b>PS</b> Polyurethane Solid	<b>Bearing Type</b>	<b>Fork Type</b>	<b>Fitting Code</b>
<b>CH</b> Chrome Hospital	<b>PC</b> Primacy Cover	<b>AM</b> Anti-Microbial TPR	<b>PW</b> White Polyurethane	<b>A</b> Annular	<b>DL</b> Directional Lock	See page 4-5 for stem codes
<b>CN</b> Chrome Neoteq	<b>PD</b> Plastic Dark Gray	<b>AP</b> Anti-static Polyurethane	<b>PY</b> Polyurethane TPU	<b>B</b> Ball	<b>DT</b> Direction/Total Comb.	<b>Fitting Type</b>
<b>CP</b> Hospital Covered	<b>PG</b> Plastic Light Gray]	<b>AR</b> Anti-static Rubber	<b>QB</b> QuickStart (dark grey tread with black thread guard)	<b>D</b> Delrin	<b>FB</b> Face Brake	<b>GR</b> Grip Ring
<b>CX</b> Chrome Hospital	<b>PP</b> Primacy Cover Precision	<b>AT</b> Anti-Static TPR	<b>QD</b> QuickStart (dark grey tread and thread guard)	<b>N</b> Plain, Nylon	<b>RB</b> Rigid Brake	<b>HK</b> Hollow Kingpin
<b>DL</b> LevelTeq Dual	<b>PS</b> Primacy Single	<b>EP</b> MedEagle	<b>QL</b> QuickStart (light grey tread and thread guard)	<b>O</b> Plain Bore	<b>RG</b> Rigid	<b>OS</b> Octagon Stem
<b>DN</b> Neoteq Dual	<b>PT</b> Primacy Twin Wheel	<b>HR</b> High Temp Rubber	<b>RM</b> Rubber on Metal	<b>P</b> Precision	<b>SB</b> Side Brake	<b>RS</b> Round Stem
<b>DW</b> Dual wheel	<b>RZ</b> Razer	<b>GR</b> Grey rubber	<b>RP</b> Rubber on Plastic	<b>R</b> Roller	<b>SW</b> Swivel	<b>SP</b> Special
<b>GT</b> Grey Tech	<b>SL</b> Streamline	<b>CR</b> Conductive Rubber	<b>RR</b> Rubber on Rubber	<b>S</b> Stainless Roller	<b>TB</b> Top Brake	<b>SQ</b> Square Stem
<b>MB</b> Med-Bed	<b>SS</b> Stainless Steel	<b>NR</b> Neoprene Rubber	<b>TP</b> Thermoplastic Rubber	<b>X</b> Stainless Precision	<b>TL</b> Total Lock	<b>CL</b> System Stem
<b>OP</b> Optimus	<b>SX</b> Stainless Hospital	<b>HS</b> Hytrel on PP				<b>TP</b> Top Plate
<b>MP</b> Marquee	<b>TA</b> Twin-Med Antistatic	<b>NY</b> Nylon		<b>Tread Width</b>		<b>TS</b> Threaded Stem
<b>MU</b> Med-Ultra	<b>TG</b> Twin-Med Grey	<b>PB</b> Polyurethane Black		<b>025</b> .25		<b>XR</b> Expanding Round
<b>NA</b> Nylon Antistatic	<b>TM</b> Twin-Med	<b>PH</b> Phenolic		<b>050</b> .50		<b>XS</b> Expanding Square
<b>ND</b> Nylon Dark Grey	<b>TU</b> Twin-Tech Ultra	<b>PP</b> Polyolefin		<b>075</b> .75		
<b>NG</b> Nylon Light Grey	<b>TW</b> Twin Wheel	<b>PR</b> Performa Rubber		<b>100</b> 1		
<b>NK</b> Nylon Black	<b>WO</b> Misc. Wheel Only			<b>125</b> 1.25		
<b>NM</b> Nylon Non-Magnetic				<b>150</b> 1.5		
<b>NS</b> Nylon Plus Stainless				<b>200</b> 2		

Wheel Diameter			
<b>01</b>	1	<b>06</b>	6
<b>02</b>	2	<b>07</b>	7
<b>03</b>	3	<b>08</b>	8
<b>35</b>	3.5	<b>24</b>	24
<b>04</b>	4		
<b>05</b>	5		

## FORK/RIG NUMBERING SYSTEM

Fork/Rig models are similar to caster models except there is no wheel code. Below is an example of a fork/rig only model for a 5" diameter by 1-1/4" tread width wheel. The fork type is swivel. The fitting type is threaded stem (1/2"-13NC x 1-1/2").

**NG-05 - 125 - SW - TS03**

## WHEEL NUMBERING SYSTEM

Wheel replacement models are similar to caster models except the last 2 digits. Below example is a wheel for a Nylon Light Grey (NG) caster that has a 5" diameter QuickStart wheel with a dark grey tread, thread guard and Precision Ball Bearing. The tread width is 1-1/4" wide. The axle is 5/16".

**NG-05 QDP-125-05**

<b>04</b>	1/4" axle
<b>05</b>	5/16" axle
<b>06</b>	3/8" axle
<b>08</b>	1/2" axle
<b>10</b>	5/8" axle
<b>12</b>	3/4" axle

