

NEXT GENERATION NYLON (NG)

ROUND/SQUARE STEM MODELS
FREE SWIVEL • TOTAL LOCK • DIRECTION LOCK



Free swivel with QuikStart wheel
NG-05QDP-125-SW-RS01




Direction Lock with Santoprene wheel
NG-05RPP-125-TL-SQ02

- APPLICATIONS**
- Food Service Equipment
 - Case Carts
 - Utility Carts
 - Medical Equipment
 - Institutional Equipment
 - Hospital Carts
 - Animal Cage Carts



Custom Colors Available



Precision sealed ball bearing raceway design for smooth, quiet maintenance free ride.

- FEATURES**
- Maintenance free
 - Sealed precision bearing raceway, smooth and quiet
 - **Total Lock Brake** models lock both swivel and wheel
 - Directional lock models lock swivel only (helps with steering)
 - Wheels feature sealed precision ball bearings and full thread guards
 - Resistance to most chemicals
 - Zinc plated top plate
 - Recessed axle with plastic cap covers

Our NG series is made of glass filled nylon for added strength and durability. Precision ball bearings are insert molded into the swivel raceway.

ROUND OR SQUARE STEM MODELS

Precision sealed ball bearing raceway design for smooth, quiet maintenance free ride.

| Wheel Diameter (Inches) | Tread Width (Inches) | Wheel Description | Capacity (Lbs) | Load Height Inches (mm) | Swivel Radius Inches (mm) | Wheel Bearing | Model Number |
|-------------------------|----------------------|--------------------|----------------|-------------------------|---------------------------|----------------|-----------------------|
| 3 | 1-1/4 | QuikStart TPR | 200 | 4-7/32" (107) | 2-13/16" (72) | Precision Ball | NG-03QDP-125-SW-_____ |
| 3 | 1-1/4 | QuikStart TPR | 200 | 4-7/32" (107) | 2-13/16" (72) | Plain | NG-03QDO-125-SW-_____ |
| 3 | 1-1/4 | Anti-Microbial TPR | 200 | 4-7/32" (107) | 2-13/16" (72) | Precision Ball | NG-03AMP-125-SW-_____ |
| 4 | 1-1/4 | QuikStart TPR | 275 | 5-13/32" (137) | 3-7/16" (87) | Precision Ball | NG-04QDP-125-SW-_____ |
| 4 | 1-1/4 | Anti-Microbial TPR | 275 | 5-13/32" (137) | 3-7/16" (87) | Precision Ball | NG-04AMP-125-SW-_____ |
| 5 | 1-1/4 | Santoprene | 260 | 6-1/2" (165) | 4" (102) | Precision Ball | NG-05RPP-125-SW-_____ |
| 5 | 1-1/4 | QuikStart TPR | 300 | 6-1/2" (165) | 4" (102) | Precision Ball | NG-05QDP-125-SW-_____ |
| 5 | 1-1/4 | Anti-Microbial TPR | 300 | 6-1/2" (165) | 4" (102) | Precision Ball | NG-05AMP-125-SW-_____ |
| 6 | 1-1/4 | QuikStart TPR | 300 | 7-1/2" (191) | 4-9/16" (116) | Precision Ball | NG-06QDP-125-SW-_____ |
| 6 | 1-1/4 | QuikStart TPR | 300 | 7-1/2" (191) | 4-9/16" (116) | Plain | NG-06QDO-125-SW-_____ |
| 6 | 1-1/4 | Anti-Microbial TPR | 300 | 7-1/2" (191) | 4-9/16" (116) | Precision Ball | NG-06AMP-125-SW-_____ |



Note: Antimicrobial casters (AMP) wheels have the darker grey fork and brighter wheel.



Rigid model available for 3", 5" and 6" diameter wheels. Change SW to RG.

Specify Round Stem (RS) code, or Square Stem code (SQ) see fittings at left for dimensions.

ROUND STEM FITTINGS

| RS01 | RS02 | RS03 | RS04 | RS05 |
|--------------|----------------|----------------|----------------|--------------|
| 45mm 22mm | 45mm 25.4mm | 45mm 27.8mm | 45mm 20.5mm | 45mm 32mm |

SQUARE STEM FITTINGS

| SQ01 | SQ02 | SQ03 |
|---------------------|---------------------|--------------------------------|
| 2" No Holes 3/4" | 1.75" 3 Holes 1" | 2.2" Square Grip Ring .850" |

See fittings page for more options.

