

General Duty

Features

- Economical mobility solution
- Zinc finish
- RoHS Compliant
- Single race
- Nut and bolt axle
- Nickel plated kingpin for smooth swivel

Applications

- Store Fixtures
- Furniture
- Material Handling
- Institutional Equipment
- Industrial Equipment

Options

- Brake: available on all swivel models (excludes steel wheel tread types). Add **[B]** to end of model number.

RoHS
Environmentally friendly

NSF listed



Wheel Selection



Soft Rubber (Black)



Hard Rubber (Dark Grey)



Polyolefin



Steel

Wheel Diameter (Inches)	Tread Width (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Type	Dynamic Load (Pounds)	Swivel Top Plate Model Number	Rigid Top Plate Model Number	Fastening Selection See page 60-62 for General Duty plate drawings.
2"	13/16"	2-1/2"	1-13/16" Brake: 2-1/8"	Soft Rubber (Black)	90	PSQ20112ZN-3R	PRQ20122ZN-3R	112 Swivel: 1-7/8" x 2-9/16" 122 Rigid: 1-1/2" x 2-21/32" Bolt Spacing: (15/16" x 2-1/8") 1/4" Bolt
				Polyolefin	125	PSQ20112ZN-3E	PRQ20122ZN-3E	
				Hard Rubber (Dark Grey)	125	PSQ20112ZN-3H	PRQ20122ZN-3H	
				Steel	125	PSQ20112ZN-STL01(GG)	PRQ20122ZN-STL01(GG)	
2-1/2"	1-1/8"	3-1/4"	2-1/4" Brake: 2-3/4"	Soft Rubber (Black)	100	PSQ25115ZN-3R	PRQ25123ZN-3R	115 Swivel: 2-3/4" x 3-7/8" Bolt Spacing: (1-3/4" x 3") 123 Rigid: 2-1/8" x 4-3/8" Bolt Spacing: (1-1/16" x 3-1/2") 5/16" Bolt
				Polyolefin	175	PSQ25115ZN-3E	PRQ25123ZN-3E	
				Hard Rubber (Dark Grey)	175	PSQ25115ZN-3H	PRQ25123ZN-3H	
				Steel	175	PSQ25115ZN-STL01(GG)	PRQ25123ZN-STL01(GG)	
3"	1-1/4"	3-13/16"	2-5/8" Brake: 3-1/4"	Soft Rubber (Black)	150	PSQ30119ZN-3R	PRQ30124ZN-3R	119 Swivel: 3-1/8" x 4-1/8" Bolt Spacing: (2-3/8" x 3-3/8" to 3-7/16") 124 Rigid: 2-5/16" x 4-7/8" Bolt Spacing: (1-3/16" x 4") 5/16" Bolt
				Polyolefin	210	PSQ30119ZN-3E	PRQ30124ZN-3E	
				Hard Rubber (Dark Grey)	225	PSQ30119ZN-3H	PRQ30124ZN-3H	
				Steel	225	PSQ30119ZN-STL01(GG)	PRQ30124ZN-STL01(GG)	
4"	1-3/8"	5"	3-7/16" Brake: 3-9/16"	Soft Rubber (Black)	200	PSQ40121ZN-3R	PRQ40125ZN-3R	121 Swivel: 4" x 5-1/8" Bolt Spacing: (3" x 4") 125 Rigid: 3-1/16" x 6-1/8" Bolt Spacing: (1-3/4" x 5") 3/8" Bolt
				Polyolefin	250	PSQ40121ZN-3E	PRQ40125ZN-3E	
				Hard Rubber (Dark Grey)	300	PSQ40121ZN-3H	PRQ40125ZN-3H	



Friction Brake
Available on swivel models except steel wheel. Add **[B]** at end of model.