Omega

Features

- Precision ball bearing wheels for smooth, quiet, and easy rollability
- · Fully heat treated
- Dual ball bearing raceways
- · High luster chrome or black finish
- Matching thread guards

Applications

- Furniture
- IV Poles
- Seating
- Medical Equipment
- · Electronic Equipment

Options

• Brakes: Tread brake uniformly integrated into body design for smooth look and ease of activation. Add [B] to end of model.

• Bolt-In Stems: available for 403 hollow kingpin models.





Wheel Selection

	Vipor	NPR	MonoTech		
Floor Protection ¹	√ +	√ +	√ +		
Non-Marking	√ +	√ +	√ +		
Durability	√ +	√ +	√ +		
Cushioned Ride	✓	√ +	√ +		

¹See page 48 for application details.

Finish Selection

Chemical Resistance





Black finish available on 3" MonoTech models; consult factory for other requirements.

MonoTech Facts

- 1. Provides ultimate floor protection and a quiet, cushioned ride.
- 2. Rolls over obstacles with ease.
- 3. Will not flat spot and is excellent on any floor type.
- 4. Rejects floor debris, including metal shavings and glass.

Dia	Vheel ameter aches)	Tread Width (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Type	Finish	Dynamic Load (Pounds) Base Model Number (Add fastening code)		Fastening Selection ²		
Г	2"	15/16"	2-3/4"	2" Brake: 2-1/2 "	Neoprene	Bright Chrome	75	POM20BC-NPR	Threaded: 507, 637, 605 Grip Ring: 223		
		15/16"	3-7/8"	2-7/8"	MonoTech	Bright Chrome	110	POM30BC-MNT	Threaded: 507, 605, 637, 74 Grip Neck: 302 Round: 419 Grip Ring: 242, 222, 223, 21		
	3"				MonoTech	Black	110	POM30BZ-MNT			
					Vipor	Bright Chrome	120	POM30BC-VPR33(CK)	Hollow Kingpin: 403 Plate: 134		

²To order, include **blue** fastener code in **Base Model Number**. Example: POM30<u>507</u>BC-MNT **Grip Neck Round Grip Ring Threaded Stem** 302 242 222 507 223 211 637 748 1-7/16 1-7/8 1 7/8" 3/8" 7/16" 7/16" 7/16" 7/16" 5/16"

Socket Options

5/16"

Shepherd has many solutions to help you mount your casters to your equipment quickly and easily. See pages 56-57 for more information










1/2"







Razer (RZ)



Features

- Attractive and economical total lock brake series with matching swivel
- Polished chrome finish
- Double ball bearing swivel raceways for smooth mobility and strength
- Full metal thread guards standard (except 2" diameter models) for protection against entangling debris
- Nut and bolt axle

Applications

- Carts
- Furniture
- Store fixtures
- Institutional equipment
- Medical equipment

Options

 Total lock brake locks both wheel and swivel action simultaneously.



Wheel Selection



Non-Marking	TPR Grey			
Floor Protection ¹	√ +			
Non-Marking	√ +			
Durability	✓			
Cushioned Ride	✓			
Chemical Resistance	✓			

¹See page 48 for application details.

Available in powder coated colors. Consult factory for minimum order quantities.



Wheel Diameter (Inches)	Tread Width (Inches)	Mounting Height (Inches)	Swivel Radius (Inches)	Tread Type	Bearing Type	Dynamic Load (Pounds)	Model Number	Total Lock Brake Base Model Number (Add fastening code)	Fastening Selection ²	
2"	3/4"	Stem: 2-3/4" Plate: 2-13/16"	1.95" Brake: 3.23"	TPR Grey	Plain	120	RZ02TPN070SW	RZ02TPN070TL	Plate: TP06	Threaded:
3"	7/8"	Stem: 3.98" Plate: 4.07"	2.85" Brake: 3.90"	TPR Grey	Ball Bearing	120	RZ03TPP090SW	RZ03TPP090TL	Plate: TP05	TS06, TS15, TS25 Grip Ring: GR01, GR02 Hollow Kingpin: HK04
4"	7/8"	Stem: 4.84" Plate: 4.92"	3.35" Brake: 4.19"	TPR Grey	Ball Bearing	120	RZ04TPP090SW	RZ04TPP090TL		
5"	7/8"	Stem: 5.95" Plate: 6.04"	3.84" Brake: 4.19"	TPR Grey	Ball Bearing	120	RZ05TPP090SW	RZ05TPP090TL		

²To order, include **blue** fastener code in **Base Model Number**. Example: RZ02TPN070SW<u>TS06</u> **Hollow Kingpin Top Plate Threaded Stem Grip Ring** HK04-TS06 **TS25 GR01** GR02 -**TS15** Bolt 1/4" 'Hole Bolt Hole 6.3mm 1" 16NC 2.12" Recommended for use with 3/8" and M10 M10 3/8" 7/16' diameter fittings. Caster comes assembled.