

# AS Bassick Honcho





Legendary Bassick Honcho casters feature sealed upper and lower raceways for additional protection from the elements. The caster legs are embossed, formed legs for added strength. Yellow dichromate finish for added corrosion resistance.

### TYPICAL APPLICATIONS

- Platform trucks
- Warehouse trucks
- Material handling containers
- Floor trucks

### MOUNTING OPTION



For rigid models change "CAS" to "CAR"

### Soft Rubber (51 Roller Bearing)

SFR	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
5	2	450	6 1/2	3 11/16		CAS50156YZ-SFR51(KK)
6	2	475	7 1/2	4 3/8		CAS60156YZ-SFR51(KK)
8	2	600	9 1/2	5 13/16		CAS80156YZ-SFR51(KK)



### Hard Rubber (51 Roller Bearing)

HDR	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
5	2	600	6 1/2	3 11/16		CAS50156YZ-HDR51(KK)
6	2	650	7 1/2	4 3/8		CAS60156YZ-HDR51(KK)
8	2	750	9 1/2	5 13/16		CAS80156YZ-HDR51(KK)



### Polyolefin (51 Roller Bearing)

POD	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	2	600	5 1/2	3		CAS40156YZ-POD51(KK)
5	2	650	6 1/2	3 11/16		CAS50156YZ-POD51(KK)
6	2	700	7 1/2	4 3/8		CAS60156YZ-POD51(KK)
8	2	900	9 1/2	5 13/16		CAS80156YZ-POD51(KK)



### Phenolic (51 Roller Bearing)

PHN	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	2	800	5 1/2	3		CAS40156YZ-PHN51(KK)
5	2	1250	6 1/2	3 11/16		CAS50156YZ-PHN51(KK)
6	2	1200	7 1/2	4 3/8		CAS60156YZ-PHN51(KK)
8	2	1250	9 1/2	5 13/16		CAS60156YZ-PHN51(KK)



### FEATURES

- **Upper/Lower Raceway Rubber seals:** Rubber swivel raceway seals help protect casters
- **Finish:** Attractive yellow dichromate finish for added corrosion resistance
- **Top Plate & Yoke Base:** Cold formed
- **Swivel Section:** Full double ball heat treated raceways. Drawn and formed ballcup
- **Fork Legs:** Embossed, formed legs for added strength
- Alternate or custom caster configurations available

### BRAKE OPTIONS

Add brake code to end of caster number

**Total Lock**  
specify -TLB



**Side Lock**  
specify -SB

**Swivel Lock**  
specify -SL



### BEARING OPTIONS

Straight Roller (51)      Sealed Roller (81)



For rigid models change "CAS" to "CAR"

### K Solid Urethane (81 Sealed Roller Bearing)

KPU	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	2	700	5 1/2	3		CAS40156YZ-KPU81(KK)
5	2	1000	6 1/2	3 11/16		CAS50156YZ-KPU81(KK)
6	2	1200	7 1/2	4 3/8		CAS60156YZ-KPU81(KK)
8	2	1250	9 1/2	5 13/16		CAS80156YZ-KPU81(KK)



### RT Reinforced Thermoplastic (51 Roller Bearing)

FRT	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	2	700	5 1/2	3		CAS40156YZ-FRT51(KK)
5	2	1000	6 1/2	3 11/16		CAS50156YZ-FRT51(KK)
6	2	1200	7 1/2	4 3/8		CAS60156YZ-FRT51(KK)
8	2	1250	9 1/2	5 13/16		CAS80156YZ-FRT51(KK)



### Eagle Urethane (51 Roller Bearing)

EAG	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	2	600	5 1/2	3		CAS40156YZ-EAG51(BK)
5	2	1100	6 1/2	3 11/16		CAS50156YZ-EAG51(BK)
6	2	1100	7 1/2	4 3/8		CAS60156YZ-EAG51(BK)
8	2	1250	9 1/2	5 13/16		CAS80156YZ-EAG51(BK)



### Urethane on Aluminum (81 Sealed Roller Bearing)

UOA	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
5	2	1250	6 1/2	3 11/16		CAS50156YZ-UOA81(BG)
6	2	1250	7 1/2	4 3/8		CAS60156YZ-UOA81(BG)
8	2	1250	9 1/2	5 13/16		CAS80156YZ-UOA81(BG)



### Steel (51 Roller Bearing)

STL	Wheel Diameter (inches)	Tread Width (inches)	Capacity (Lbs)	Overall Height (inches)	Swivel Lead (inches)	Caster Number
4	2	1200	5 1/2	3		CAS40156YZ-STL51(GG)
5	2	1250	6 1/2	3 11/16		CAS50156YZ-STL51(GG)
6	2	1250	7 1/2	4 3/8		CAS60156YZ-STL51(GG)
8	2	1250	9 1/2	5 13/16		CAS80156YZ-STL51(GG)

